

STK400 一般構造用炭素鋼管 STPY400 配管用アーク溶接炭素鋼管①

外径	肉厚	外径	肉厚	外径	肉厚	外径	肉厚
21.7	1.9	101.6	3.2	216.3	4.5	406.4	6.0
	2.3		3.5		5.8		6.4
	2.8		4.2		7.0		7.9
27.2	1.9	114.3	5.7	241.8	8.2	457.2	9.0
	2.3		8.1		10.3		9.5
	2.8		3.5		12.7		12.7
34.0	3.9	139.8	4.5	267.4	15.0	508.0	16.0
	2.3		6.0		6.2		19.0
42.7	3.2	165.2	8.6	318.5	4.5	558.8	22.0
	2.3		3.5		5.8		6.0
	2.8		4.0		6.0		6.4
	3.2		4.5		6.6		7.9
48.6	3.5	190.7	6.0	355.6	7.8	558.8	9.5
	2.3		6.6		8.0		12.7
	2.8		8.1		9.3		14.3
	3.2		9.5		12.7		16.0
60.5	3.5	216.3	11.0	267.4	15.1	406.4	19.0
	5.1		3.5		6.0		22.0
	2.3		3.7		6.9		23.8
	2.8		4.5		7.9		6.0
	3.2		5.0		9.0		6.4
	3.8		6.0		9.5		7.9
76.3	4.9	241.8	7.1	267.4	10.3	406.4	9.5
	5.5		9.3		12.7		12.7
	2.8		11.0		14.3		16.0
	3.2		4.5		17.4		19.0
	4.2		5.3		6.0		20.6
89.1	5.2	267.4	6.0	318.5	6.4	457.2	22.0
	6.0		7.0		7.9		6.4
	7.0		11.0		9.5		7.9
	2.8				11.1		9.5
89.1	3.2	267.4		267.4	12.7	406.4	12.7
	4.2				16.0		16.0
	5.5				19.0		19.0
89.1	7.6						22.0

STK400 一般構造用炭素鋼管 STPY400 配管用アーク溶接炭素鋼管②

外径	肉厚	外径	肉厚	
609.6	6.0	863.6	7.9	
	6.4		9.5	
	7.9		12.7	
	9.5		16.0	
	12.7	914.4	7.9	
	16.0		9.5	
	19.0		12.7	
	22.0		16.0	
660.4	6.4	1016.0	22.0	
	7.9		7.9	
	9.5		8.7	
	12.7		9.5	
	16.0		12.7	
	19.0		16.0	
711.2	6.0	1117.6	19.0	
	6.4		22.0	
	7.9		9.5	
	9.5		10.3	
	12.7	12.7		
	16.0	1219.2	9.5	
	19.0		11.1	
	22.0		12.7	
	16.0			
762.0	6.4			
	7.9			
	9.5			
	12.7			
	16.0			
812.8	6.4			
	7.9			
	9.5			
	12.7			
	16.0			
	19.0			
	22.0			