

STKM13A 機械構造用炭素鋼鋼管①

外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ				
27.2	5.5	5,500	40.0	5.0	6,000	48.6	5.5	6,000	55.0	4.0	6,000				
	7.8	6,000		6.0			6.0			5.0					
30.0	5.0	6,000		7.0			6.5			6.0					
	6.0			8.0		7.1	5,500	7.0							
31.8	3.2	6,000		10.0		8.0	6,000	8.0		8.0		8.0	8.0	8.0	
	3.5			12.0		9.0		9.0		10.0		10.0			
	4.0			42.7		4.5		10.0		10.0		10.0	12.0	12.0	12.0
	4.5					5.0		12.0		12.0		12.0	15.0	15.0	
	5.0					5.5		13.5		13.5		13.5	18.0	18.0	
	5.5					6.0		15.0		15.0		15.0	57.0	3.2	6,000
	6.0		6.4		5,500	50.8		3.5	6,000	4.0	4.0				
	7.0		7.0		6,000			4.0		5.0					
	8.0		8.0		8.0			4.5		6.0					
	10.0		9.0		9.0			5.0		7.0					
34.0	5.0	6,000	10.0	6.0	6,000		6.0	6.0		6.0	6.0	6.0			
	5.5		12.0	7.0			7.0	7.0							
	6.0		15.0	8.0			8.0	8.0							
	6.4		45.0	3.5			9.0	9.0		9.0	10.0	10.0			
	7.0			4.0		10.0	10.0	10.0	12.0	12.0					
	8.0			4.5		11.0	11.0	11.0	15.0	15.0					
9.0	5.0	12.0		12.0	12.0	60.5	5.0	6,000							
10.0	6.0	15.0	15.0	15.0	5.5										
38.1	3.5	6,000	7.0	6.0	6,000	54.0	18.0	6,000	7.0	7.0	7.0				
	4.0		8.0	8.0			8.0		8.0	8.0	8.0				
	4.5		9.0	9.0			9.0		9.0	8.7	5,500				
	5.0		10.0	10.0			10.0		10.0	10.0	6,000				
	5.5		12.0	12.0			12.0		12.0	11.0	11.0				
	6.0		15.0	15.0			15.0		15.0	12.0	12.0				
	7.0						9.0	9.0	9.0	13.0	13.0				
	8.0						10.0	10.0	10.0	15.0	15.0				
	9.0						11.0	11.0	11.0	18.0	18.0				
	10.0						12.0	12.0	12.0	20.0	20.0				
	12.0														

STKM13A 機械構造用炭素鋼鋼管②

外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ	
63.5	3.2	6,000	73.0	5.0	6,000	80.0	5.0	5,500	89.1	6.0	6,000	
	4.0			6.0			6,000	7.0				
	5.0			7.0			8.0	8.0				
	6.0			8.0			9.0	9.0				
	7.0			10.0			10.0	10.0				
	8.0			12.0			11.0	11.0				
	9.0			13.5			12.0	11.1		5,500		
	10.0			14.0			15.0	12.0		6,000		
	12.0			15.0			17.0	13.0				
	15.0			18.0			18.0	15.0				
	18.0			20.0			20.0	16.0				
	20.0			25.0			22.0	17.0				
	25.0			25.0			25.0	18.0				
	65.0			4.0			6,000	76.3		6.0		6,000
5.0		6.0	6.0	7.0								
6.0		7.0	7.0	8.0								
7.0		8.0	8.0	9.0								
8.0		9.5	5,500	10.0								
10.0		10.0	6,000	12.0								
12.0		11.0	13.0	12.0								
15.0		12.0	14.0	15.0								
18.0		13.0	15.0	16.0								
20.0		14.0	18.0	18.0								
25.0		15.0	20.0	20.0								
25.0		16.0	22.0	22.0								
25.0		18.0	25.0	25.0								
70.0		4.0	6,000	76.3	15.0	6,000			85.0	5.0	6,000	
	5.0	16.0			6.0		6.5					
	6.0	18.0			7.0		7.0	5,500				
	7.0	20.0			8.0		8.0	6,000				
	8.0	22.0			10.0		10.0					
	9.0	25.0			12.0		12.0					
	10.0	25.0			15.0		15.0					
	11.0	25.0			18.0		18.0					
	12.0	25.0			20.0		20.0					
	13.0	25.0			22.0		22.0					
	15.0	25.0			25.0		25.0					
	18.0	25.0			25.0		25.0					
	20.0	25.0			25.0		25.0					
	22.0	25.0			25.0		25.0					
25.0	25.0	25.0	25.0									

STKM13A 機械構造用炭素鋼鋼管③

外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ			
101.6	7.0	6,000	110.0	5.0	6,000	120.0	5.0	6,000	130.0	5.0	6,000			
	8.0			6.0			6.0			6.0				
	10.0			7.0			7.0			7.0				
	11.0			8.0			7.5			6,500		6.5	6,500	
	12.0			9.0			8.0			6,000		7.0	6,000	
	12.7			5,500			10.0			10.0		8.0	8.0	
	14.0			4,610			12.0			12.0		10.0	10.0	
	15.0			6,000			15.0			15.0		12.0	12.0	
	16.0			18.0			18.0			18.0		15.0	15.0	
	17.0			20.0			20.0			20.0		18.0	18.0	
	18.0	22.0		22.0	22.0		20.0	20.0						
	20.0	25.0		25.0	25.0		22.0	22.0						
	22.0	30.0		30.0	30.0		25.0	25.0						
	25.0	35.0		35.0	35.0		30.0	30.0						
	30.0	114.3		8.0	6,000		124.0	8.0		6,000	40.0	40.0	40.0	
	105.0	6.0		6,000	10.0		6,000	127.0		4.5	6,000	132.0	8.0	6,500
		7.0			11.0			5.0		133.0		7.0	6,500	
8.0		11.1	6.0		135.0	7.0		6,000						
10.0		12.0	7.0		8.0	8.0		8.0						
12.0		13.5	5,500		10.0	9.0		9.0						
15.0		15.0	6,000		11.0	10.0		10.0						
18.0		16.0	12.0		12.0	12.0		12.0						
20.0		17.0	15.0		15.0	15.0		15.0						
22.0		18.0	18.0		18.0	18.0		18.0						
25.0		20.0	20.0		20.0	20.0		20.0						
30.0		22.0	22.0		22.0	25.0		25.0						
		25.0	25.0		25.0	30.0		30.0						
		28.0	28.0		28.0	35.0		35.0						
	30.0	30.0	30.0	40.0	40.0									
	35.0	35.0	35.0	136.0	7.0	6,500								

STKM13A 機械構造用炭素鋼鋼管⑤

外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ	外径	肉厚	長さ				
180.0	8.0	6,500	193.7	8.0	6,500	210.0	8.0	6,500	225.0	8.0	6,500				
	10.0	6,000		10.0			6,000			10.0		6,000			
	12.0			12.0			6,500			12.0		6,500			
	15.0			15.0			6,000			15.0		6,000			
	18.0			18.0						18.0					
	20.0	6,500		20.0						20.0					
	25.0			25.0						25.0					
	30.0			30.0						30.0					
	35.0			35.0						35.0					
	40.0			40.0						40.0		6,000			
185.0	8.0	6,000	196.4	8.0	6,500	216.3	8.0	6,500	227.0	8.0	6,500				
	10.0			200.0	8.0		6,500			10.0			10.0	6,500	
	12.0				40.0					12.0			12.0	6,500	
	15.0		203.0	8.0	6,500		15.0					15.0			
	20.0			10.0						18.2			18.2		
	25.0	6,500		12.0						20.0			20.0		
	30.0						15.0					23.0		23.0	
	35.0	6,000		18.0						25.0			25.0		
	40.0						20.0					28.0		28.0	
							25.0					30.0		30.0	
187.0	8.0	6,500		25.0		35.0		35.0							
190.7	6.0	6,000		30.0		40.0		40.0		40.0					
	7.0			35.0		45.0	6,000	45.0		45.0					
	8.0	6,500		40.0		50.0			50.0	6,000					
	9.0	6,000	205.0	8.0	6,500	219.1	8.0	6,500	241.8	8.0	6,500				
	10.0						10.0					10.0			
	11.0						12.0					12.0			
	12.0						15.0					15.0			
	15.0			6,500			18.0					18.0			
	18.0									20.0			20.0		
	20.0									22.0			25.0		
22.0							25.0					30.0			
25.0		30.0		35.0											
30.0		35.0		40.0											
35.0		40.0		45.0	6,000										
40.0		45.0		45.0											
45.0		208.0	8.0	6,500			50.0	6,000							

STKM13A 機械構造用炭素鋼鋼管⑦

外径	肉厚	長さ	外径	肉厚	長さ
365.1	12.0	6,500	426.0	12.0	6,500
	15.0				
	20.0				
	25.0				
	30.0				
	35.0				
	40.0	6,000			
	50.0	6,500			
	60.0	6,000			
381.0	10.0	6,500			
	12.0				
	15.0				
	20.0				
	25.0				
	30.0				
	35.0				
	40.0				
	45.0				
	50.0				
406.4	12.0	6,500			
	15.0				
	20.0				
	21.4				
	25.0				
	26.2				
	30.0				
	30.9				
	35.0				
	36.5				
	40.0				
	40.5				
	45.0				
	50.0				
	55.0	6,000			
60.0	6,500				